

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor

**Description** AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

**Pattern Name**      **AGRIMAX RT 657**

Version                    STANDARD  
 US Code                   94028528  
 Type                        TL  
 Tire Size                  480/65 R 24  
 LI/SS                      140 D/143 A8



**Dimensions (U/M US Standard)**

Section Width (in)      18.9  
 Overall Diameter (in)    48.6  
 Static Loaded Radius (in) 22.1  
 Rolling Circumference (in) 146.9  
 SRI                         600  
 Rim Rec                    W 15 L  
 Rim Alt                     W 14 L  
 ECE                         E4-106R-000617  
 TRA Code                 R-1W

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23	29	35
40	2650	3090	3470	3860	4240	4570	5070	5510
30	2780	3240	3650	4060	4460	4810	5320	5790
25	2890	3370	3790	4210	4630	4990	5530	6010
20	3040	3550	4000	4440	4880	5270	5830	6340
5 LT	3550	4140	4660	5170	5690	6140	6800	7390
5 HT	3040	3550	4000	4440	4880	5270	5830	6340