

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 US Code 94028535
 Type TL
 Tire Size 480/65 R 28
 LI/SS 142 D/145 A8



Dimensions (U/M US Standard)

Section Width (in) 18.9
 Overall Diameter (in) 52.6
 Static Loaded Radius (in) 24.0
 Rolling Circumference (in) 159.8
 SRI 650
 Rim Rec W 15 L
 Rim Alt W 14 L
 ECE E4-106R-000653

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	2810	3270	3680	4090	4510	4850	5380	5840
30	2950	3440	3870	4300	4730	5100	5650	6140
25	3080	3580	4030	4480	4930	5310	5890	6390
20	3230	3770	4240	4710	5180	5590	6190	6720
5 LT	3770	4400	4940	5490	6040	6510	7220	7840
5 HT	3230	3770	4240	4710	5180	5590	6190	6720