

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

**Pattern Name      AGRIMAX RT 955**

Version: STANDARD  
 US Code: 94028610  
 Type: TL  
 Tire Size: 230/95 R 42  
 LI/SS: 133 A8/B



Dimensions (U/M US Standard)  
 Section Width (in): 9.4  
 Overall Diameter (in): 59.3  
 Static Loaded Radius (in): 28.1  
 Rolling Circumference (in): 182.4  
 SRI: 725  
 Rim Rec: W 8  
 Rim Alt: W 7

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
25	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
20	1900	2480	3020	3310	3510	3850	4190	4530	4860	-
5	2120	2670	3270	3890	4500	4640	5180	5730	6270	6810