

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 Type TL
 Tire Size 440/65 R 28
 LI/SS 138 D/141 A8



Dimensions (U/M International standard)

Section Width (mm) 441
 Overall Diameter (mm) 1283
 Static Loaded Radius (mm) 590
 Rolling Circumference (mm) 3878
 SRI 625
 Rim Rec W 14 L
 Rim Alt W 13 ; W 15 L

LOAD CAPACITY TABLE (kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1135 | 1325 | 1490 | 1655 | 1820 | 1960 | 2175 | 2360 |
| 50 | 1195 | 1390 | 1565 | 1740 | 1910 | 2060 | 2285 | 2480 |
| 40 | 1240 | 1445 | 1625 | 1805 | 1985 | 2140 | 2370 | 2575 |
| 30 | 1305 | 1525 | 1715 | 1905 | 2095 | 2255 | 2500 | 2715 |
| 10 LT | 1520 | 1775 | 1995 | 2220 | 2440 | 2630 | 2915 | 3165 |
| 10 HT | 1305 | 1525 | 1715 | 1905 | 2095 | 2255 | 2500 | 2715 |