

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 US Code 94029150
 Type TL
 Tire Size 540/65 R 30
 LI/SS 150 D/153 A8



Dimensions (U/M US Standard)

Section Width (in) 20.9
 Overall Diameter (in) 57.6
 Static Loaded Radius (in) 26.4
 Rolling Circumference (in) 173.3
 SRI 700
 Rim Rec W 16 L
 Rim Alt W 18 L
 ECE E4-106R-000651
 TRA Code R-1W

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3550	4140	4660	5170	5690	6140	6800	7400
30	3730	4350	4890	5430	5990	6450	7140	7760
25	3870	4510	5070	5630	6210	6680	7410	8050
20	4090	4760	5360	5950	6550	7050	7830	8500
5 LT	4760	5540	6240	6930	7630	8220	9120	9900
5 HT	4090	4760	5360	5950	6550	7050	7830	8500