

TECHNICAL SPECIFICATION

Applications: Trailer / Hay Harvester / Baler
 Description: FLOTATION 648 T is particularly suitable for field and road transport as well as for hay harvesting. Its tread design allows for carrying very high loads at low pressure and ensures outstanding self-cleaning properties. In line with BKT's commitment to provide products supporting the farming business, FLOTATION 648 T maximizes your yield and takes care of the land.

Pattern Name **FLOTATION 648 T**

Version: STANDARD
 US Code: 94029242
 Type: TL
 Tire Size: 550/45 - 22.5
 PR: 20

Dimensions (U/M US Standard)
 Section Width (in): 21.7
 Overall Diameter (in): 42.1
 Static Loaded Radius (in): 18.7
 Rolling Circumference (in): 126.1
 Rim Rec: AG 16.00



LOAD CAPACITY TABLE (lbs)

mph / psi	44	51	58
5 FR	13820	15120	16360
10 FR	12440	13610	14730
20 FR	11070	12100	13080
25 FR	9880	10800	11680
30 FR	8880	9720	10470
5 DW	9790	10710	11570
10 DW	8810	9630	10420
20 DW	7830	8560	9260
25 DW	6990	7650	8270
30 DW	6290	6890	7390

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%