

TECHNICAL SPECIFICATION

Applications Spreader / Harvester
 Description Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

Pattern Name AGRIMAX TERIS

Version STANDARD
 US Code 94029723
 Type TL
 Tire Size 900/60 R 32 CHO
 LI/SS 181 A8/178 B



Dimensions (U/M US Standard)
 Section Width (in) 34.9
 Overall Diameter (in) 74.5
 Static Loaded Radius (in) 33.1
 Rolling Circumference (in) 225.8
 SRI 925
 Rim Rec DW 27 B
 Rim Alt DW 28 B ; DW 30 B

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	7440	8430	10580	11740	13060	14050	15380	16530
25	8190	9280	11640	12920	14370	15460	16920	18190
20	8760	9930	12470	13820	15390	16560	18110	19470
10 Cyc.	13510	15310	19210	21320	23720	25520	27920	30010
5 Cyc.	14740	16700	20950	23250	25870	27830	30460	32740