

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94029747
 Type: TL
 Tire Size: 300/95 R 52
 LI/SS: 151 A8/B

Dimensions (U/M US Standard)

Section Width (in): 11.6
 Overall Diameter (in): 74.4
 Static Loaded Radius (in): 35.0
 Rolling Circumference (in): 229.2
 SRI: 925
 Rim Rec: W 9
 Rim Alt: W 10 ; W 11 ; DW 10 ; DW 11



LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
25	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
20	3190	4160	5060	5540	5870	6440	7010	7580	8150	-
5	3540	4450	5480	6500	7540	7760	8670	9590	10500	11410