

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor / Sprayer

**Description** AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name**      **AGRIMAX RT 855**

Version                    STANDARD  
 US Code                    94029914  
 Type                        TL  
 Tire Size                    480/80 R 50  
 LI/SS                        159 A8/B

**Dimensions (U/M US Standard)**

Section Width (in)        19.3  
 Overall Diameter (in)    80.2  
 Static Loaded Radius (in) 37.0  
 Rolling Circumference (in) 242.4  
 SRI                         975  
 Rim Rec                    DW 16 A  
 Rim Alt                     DW 15 A ; W 15 A



**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23	29	35
30	4540	5210	5990	6760	7530	8300	8970	9640
25	4540	5210	5990	6760	7530	8300	8970	9640
20	4860	5580	6400	7230	8060	8880	9610	10330
5 LT	6080	6990	8020	9060	10090	11120	12030	12930
5 HT	4860	5580	6400	7230	8060	8880	9610	10330