

TECHNICAL SPECIFICATION

Applications Forestry Harvester

Description TR 678 has been specially designed for forestry applications. Its robust lug design provides excellent traction and self-cleaning. The strong casing structure stands for high load capacity whereas its steel belts protect the tire from punctures and damages. TR 678 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains under extreme conditions.

Pattern Name **TR 678**

Version STEEL BELTED

US Code 94030170

Type TL

Tire Size 650/45 - 22.5

LI/SS 166 B

PR 20



Dimensions (U/M US Standard)

Section Width (in) 25.6

Overall Diameter (in) 45.3

Static Loaded Radius (in) 19.8

Rolling Circumference (in) 130

Rim Rec 20.0

LOAD CAPACITY TABLE (lbs)

mph / psi	65
30	11680

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..