

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
 US Code 94030569
 Type TL
 Tire Size 520/85 R 46
 LI/SS 158 A8/B



Dimensions (U/M US Standard)

Section Width (in) 20.3
 Overall Diameter (in) 80.8
 Static Loaded Radius (in) 37.4
 Rolling Circumference (in) 246.1
 SRI 975
 Rim Rec DW 16 L ; W 16 A ; W 16 L ; DD 16
 Rim Alt DW 18 L ; W 18 L ; W 18 A

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23
30	5160	6000	6840	7680	8530	9370
25	5160	6000	6840	7680	8530	9370
20	5520	6430	7330	8230	9140	10030
5 LT	6910	8040	9170	10300	11430	12550
5 HT	5520	6430	7330	8230	9140	10030