

**TECHNICAL SPECIFICATION**

Applications                    Tractor  
 Description                    TR 270 is a tractor tire suitable for soil tillage applications. It is specially designed for providing maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning features. TR 270 perfectly meets all these characteristics.

**Pattern Name            TR 270**

Version                        STANDARD  
 US Code                      94031030  
 Type                            TT  
 Tire Size                     23.1 - 34  
 LI/SS                         156 A8  
 PR                              14



Dimensions (U/M US Standard)  
 Section Width (in)        23.2  
 Overall Diameter (in)    72.8  
 Static Loaded Radius (in) 33.1  
 Rolling Circumference (in) 217.8  
 Rim Rec                     DW 20 A ; DW 20 B

**LOAD CAPACITY TABLE (lbs)**

<b>mph / psi</b>	<b>32</b>
25	8820

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.  
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..