

TECHNICAL SPECIFICATION

Applications Loader
 Description ROCK GRIP (L-4) is a bias-ply tire designed for wheel loader operations in severe loading service and on rough ground conditions. Its specially designed, cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The (L-4) tread depth provides an extended tire life-cycle.

Pattern Name ROCK GRIP L4

Version STANDARD
 US Code 94031214
 Type TT
 Tire Size 14.00 - 25
 PR 24



Dimensions (U/M US Standard)
 Overall Diameter (in) 55.5
 Static Loaded Radius (in) 25.6
 Rolling Circumference (in) 164.3
 Rim Rec 10.00/1.5

LOAD CAPACITY TABLE (lbs)

mph / psi	123
5	20940

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..