

## TECHNICAL SPECIFICATION

**Applications** Telehandler / Compact Loader / Backhoe Loader

**Description** MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

**Pattern Name** **MULTIMAX MP 522**

**Version** STANDARD  
**US Code** 94031313  
**Type** TL  
**Tire Size** 460/70 R 24 IND  
**LI/SS** 159 A8/B

**Dimensions (U/M US Standard)**

**Section Width (in)** 18.3  
**Overall Diameter (in)** 49.2  
**Static Loaded Radius (in)** 22.4  
**Rolling Circumference (in)** 148.3  
**SRI** 600  
**Rim Rec** DW 15 L  
**Rim Alt** DW 14 L ; DW 16 L  
**ECE** E4-106R-002396



**LOAD CAPACITY TABLE (lbs)**

mph / psi	23	29	35	41	46	51	58	61	64
30	4630	5500	6270	7140	8010	8590	9650	-	-
25	4630	5500	6270	7140	8010	8590	9650	-	-
20	4960	5900	6720	7650	8580	9190	10330	-	-
15	5150	6120	6970	7940	8900	9550	10710	-	-
5 Cyc	5650	6960	8180	9410	10710	11650	13170	13900	14470
Static	8660	10660	12540	14430	16420	17870	20190	21310	22190