

TECHNICAL SPECIFICATION

Applications Spreader / Harvester
 Description Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

Pattern Name AGRIMAX TERIS

Version STANDARD
 US Code 94031412
 Type TL
 Tire Size 800/65 R 32 CHO
 LI/SS 178 A8/175 B



Dimensions (U/M US Standard)
 Section Width (in) 32.2
 Overall Diameter (in) 73.0
 Static Loaded Radius (in) 33.0
 Rolling Circumference (in) 220
 SRI 875
 Rim Rec DW 27 B
 Rim Alt DW 25 B ; DH 27 B

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	7000	8070	9890	10800	12030	12930	14150	15210
25	7610	8760	10750	11740	13060	14050	15380	16530
20	8150	9380	11510	12570	13980	15050	16460	17690
10 Cyc.	12550	14460	17740	19380	21560	23190	25370	27280
5 Cyc.	13690	15770	19340	21130	23510	25300	27680	29760