

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 Type TL
 Tire Size 600/65 R 28
 LI/SS 154 D/157 A8

Dimensions (U/M International standard)

Section Width (mm) 611
 Overall Diameter (mm) 1491
 Static Loaded Radius (mm) 670
 Rolling Circumference (mm) 4470
 SRI 700
 Rim Rec DW 20 B
 Rim Alt W 18 L



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1800	2100	2365	2625	2890	3115	3450	3750
50	1895	2210	2485	2760	3035	3275	3625	3940
40	1980	2310	2600	2890	3180	3425	3795	4125
30	2075	2420	2720	3025	3325	3585	3970	4315
10 LT	2415	2815	3170	3520	3870	4175	4625	5025
10 HT	2075	2420	2720	3025	3325	3585	3970	4315