

**TECHNICAL SPECIFICATION**

Applications Rotor Rake / Tedder / Forklift  
 Description PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

**Pattern Name PL 801**  
 Version STANDARD  
 US Code 94032259  
 Type TT  
 Tire Size 5.00 - 8  
 PR 10



Dimensions (U/M US Standard)  
 Section Width (in) 5.3  
 Overall Diameter (in) 18.4  
 Rim Rec 3.00 D  
 Rim Alt 3.25 I

**LOAD CAPACITY TABLE (lbs)**

mph / psi	145
15 LOAD WHEEL	3120
15 STEER WHEEL	2405
5 OTHER VEHICLES	3120
15 OTHER VEHICLES	2405
STATIC SIDE LOADER	3625

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..