

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
Type TL
Tire Size 600/65 R 30
LI/SS 155 D/158 A8

Dimensions (U/M International standard)

Section Width (mm) 611
Overall Diameter (mm) 1542
Static Loaded Radius (mm) 697
Rolling Circumference (mm) 4609
SRI 725
Rim Rec DW 20 B
Rim Alt W 18 L



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1860	2170	2445	2715	2985	3220	3565	3875
50	1955	2280	2565	2850	3135	3380	3745	4070
40	2040	2380	2680	2975	3275	3530	3910	4250
30	2145	2500	2810	3125	3435	3705	4105	4460
10 LT	2495	2910	3275	3640	4005	4315	4780	5195
10 HT	2145	2500	2810	3125	3435	3705	4105	4460