

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 US Code 94032327
 Type TL
 Tire Size 600/65 R 34
 LI/SS 157 D/160 A8



Dimensions (U/M US Standard)

Section Width (in) 24.1
 Overall Diameter (in) 64.7
 Static Loaded Radius (in) 29.2
 Rolling Circumference (in) 195.3
 SRI 775
 Rim Rec DW 20 B
 Rim Alt W 18 L
 ECE E4-106R-001405
 TRA Code R-1W

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4360	5090	5730	6370	7010	7550	8370	9100
30	4600	5360	6030	6690	7360	7940	8800	9560
25	4760	5560	6250	6940	7640	8230	9130	9920
20	5030	5860	6590	7330	8060	8690	9630	10460
5 LT	5850	6830	7680	8540	9390	10120	11220	12190
5 HT	5030	5860	6590	7330	8060	8690	9630	10460