

TECHNICAL SPECIFICATION

Applications Trailer
 Description FARM HIGHWAY TOUGH is a high-speed tire designed for transport applications with trailers. It provides high load capacity to improve your productivity and ensures a long tire life-cycle.

Pattern Name FARM HIGHWAY TOUGH

Version STANDARD
 US Code 94032525
 Type TL
 Tire Size 12.5L - 15 FI
 PR 12



Dimensions (U/M US Standard)
 Section Width (in) 12.5
 Overall Diameter (in) 32.1
 Static Loaded Radius (in) 14.3
 Rolling Circumference (in) 91.5
 Rim Rec 10 LB

LOAD CAPACITY TABLE (lbs)

mph / psi	90
62	4680

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..