

TECHNICAL SPECIFICATION

Applications: Spreader / Harvester
 Description: Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

Pattern Name AGRIMAX TERIS

Version: STANDARD
 US Code: 94032723
 Type: TL
 Tire Size: 1050/50 R 32 CHO
 LI/SS: 184 A8/181 B



Dimensions (U/M US Standard)
 Section Width (in): 41.7
 Overall Diameter (in): 74.5
 Static Loaded Radius (in): 33.1
 Rolling Circumference (in): 223.8
 SRI: 875
 Rim Rec: 36.0 VA

LOAD CAPACITY TABLE (lbs)

| mph / psi | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 8190 | 9280 | 11640 | 12920 | 14370 | 15460 | 16920 | 18190 |
| 25 | 8930 | 10120 | 12700 | 14090 | 15670 | 16860 | 18450 | 19840 |
| 20 | 9560 | 10840 | 13590 | 15080 | 16780 | 18050 | 19750 | 21230 |
| 10 Cyc. | 14740 | 16700 | 20950 | 23250 | 25870 | 27830 | 30460 | 32740 |
| 5 Cyc. | 16070 | 18220 | 22860 | 25360 | 28220 | 30360 | 33220 | 35710 |