

**TECHNICAL SPECIFICATION**

Applications                      Spreader / Harvester  
 Description                      Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**Pattern Name                      AGRIMAX TERIS**

Version                              STANDARD  
 US Code                            94032860  
 Type                                 TL  
 Tire Size                          650/75 R 32 CHO  
 LI/SS                                172 A8/B



Dimensions (U/M US Standard)  
 Section Width (in)              25.8  
 Overall Diameter (in)          70.4  
 Static Loaded Radius (in)      31.3  
 Rolling Circumference (in)    209.6  
 SRI                                  825  
 Rim Rec                            DW 21 B  
 Rim Alt                             DW 20 B ; DW 23 B

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	15	20	23	29	35	41	46
30	6390	7360	9030	9870	10840	11810	12790	13890
25	6390	7360	9030	9870	10840	11810	12790	13890
20	6840	7880	9670	10560	11610	12640	13690	14870
10 Cyc.	10550	12150	14900	16280	17880	19490	21090	22920
5 Cyc.	11510	13260	16260	17760	19510	21250	23000	25000