

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version SPECIAL
 US Code 94033188
 Type TL
 Tire Size 300/95 R 52
 LI/SS 151 A8/B

Dimensions (U/M US Standard)

Section Width (in) 11.6
 Overall Diameter (in) 74.4
 Static Loaded Radius (in) 35.0
 Rolling Circumference (in) 229.2
 SRI 925
 Rim Rec W 9
 Rim Alt W 10 ; W 11 ; DW 10 ; DW 11



LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
25	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
20	3190	4160	5060	5540	5870	6440	7010	7580	8150	-
5	3540	4450	5480	6500	7540	7760	8670	9590	10500	11410