

TECHNICAL SPECIFICATION

Applications: Telehandler / Compact Loader / Backhoe Loader

Description: MULTIMAX MP 522 is the BKT multi-purpose tire developed for manifold agro-industrial applications. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders. Stability and high load capacity are its strengths as well as outstanding puncture resistance. Multimax MP 522 is the right response for all agro-industrial heavy-duty needs.

Pattern Name **MULTIMAX MP 522**

Version: STANDARD
 US Code: 94033829
 Type: TL
 Tire Size: 400/70 R 20 IND
 LI/SS: 149 A8/B



Dimensions (U/M US Standard)

Section Width (in): 15.9
 Overall Diameter (in): 42.0
 Static Loaded Radius (in): 18.7
 Rolling Circumference (in): 125.9
 SRI: 525
 Rim Rec: 13
 Rim Alt: 12 SDC ; 13 SDC ; 14
 ECE: E4-106R-002319

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	3440	4090	4660	5300	5950	6380	7160	-	-
25	3440	4090	4660	5300	5950	6380	7160	-	-
20	3690	4380	4990	5690	6370	6830	7670	-	-
15	3820	4540	5180	5900	6610	7090	7960	-	-
5 Cyc	4200	5160	6070	6990	7960	8650	9790	10320	10750
Static	6440	7910	9310	10710	12200	13270	15000	15830	16480