

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader
 Description: FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle.

Pattern Name **FL 639**
 Version: STANDARD
 US Code: 94034260
 Type: TL
 Tire Size: 560/45 R 22.5
 LI/SS: 152 D/163 A8



Dimensions (U/M US Standard)
 Section Width (in): 21.4
 Overall Diameter (in): 42.4
 Static Loaded Radius (in): 19.1
 Rolling Circumference (in): 130
 SRI: 525
 Rim Rec: AG 16.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2290	2650	3000	3570	4210	4780	5360	6000	6570	7130
40	2510	2910	3300	3950	4620	5250	5950	6530	7210	7830
30	3040	3520	3990	4740	5600	6390	7140	7970	8730	9480
25	3440	3980	4520	5400	6350	7210	8100	9020	9890	10750
15	3970	4590	5200	6220	7300	8320	9330	10360	11390	12370
5	4510	5210	5920	7050	8320	9480	10630	11790	12960	14090