

## TECHNICAL SPECIFICATION

**Applications** Trailer / Tanker / Spreader

**Description** RIDEMAX FL 690 is a radial flotation and transport tire for tank trucks, trailers and spreaders. The tire is suitable for 75% on-the-road applications. Its special tread design provides outstanding self-cleaning properties in the field. As a response to the increasing demand for high loads in modern agriculture, BKT has designed this steel-belted tire withstanding very heavy loads and increasing the farmer's productivity.

**Pattern Name** **RIDEMAX FL 690**

**Version** STANDARD  
**US Code** 94034321  
**Type** TL  
**Tire Size** 28L R 26  
**LI/SS** 176 A8/173 B

**Dimensions (U/M US Standard)**

**Section Width (in)** 28.3  
**Overall Diameter (in)** 62.6  
**Static Loaded Radius (in)** 27.4  
**Rolling Circumference (in)** 186.8  
**SRI** 750  
**Rim Rec** DW 25 B  
**Rim Alt** DW 23 B  
**ECE** E11-106R-002985



**LOAD CAPACITY TABLE (lbs)**

| mph / psi | 12    | 15    | 20    | 23    | 29    | 35    | 41    |
|-----------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 6880  | 7850  | 9530  | 10320 | 11750 | 13040 | 14330 |
| 25        | 7520  | 8560  | 10420 | 11280 | 12840 | 14250 | 15650 |
| 20        | 8420  | 9600  | 11670 | 12630 | 14380 | 15960 | 17540 |
| 15        | 8950  | 10200 | 12390 | 13410 | 15280 | 16950 | 18630 |
| 5         | 10530 | 11990 | 14580 | 15780 | 17980 | 19950 | 21910 |