

## **TECHNICAL SPECIFICATION**

Applications Trailer / Tanker / Spreader

Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance

contributes to less fuel consumption.

## **Pattern Name RIDEMAX FL 693 M**

STANDARD Version US Code 94034505 Туре

Tire Size 850/50 R 30.5

LI/SS 182 D

Dimensions (U/M US Standard) Section Width (in) Overall Diameter (in) 64.0 Static Loaded Radius (in) 28.3 Rolling Circumference (in) 193.9 SRI 725 AG 28.00 Rim Rec



## LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	6320	7160	8700	10060	11600	13140	14160	15700	17050
40	6930	7870	9560	11060	12740	14430	15550	17240	18740
30	8400	9520	11570	13380	15420	17460	18830	20870	22670
25	9440	10710	13010	15050	17340	19630	21150	23460	25480
15	10970	12440	15100	17470	20140	22810	24580	27250	29610
5	12490	14170	17210	19910	22940	25980	28000	31040	33730