

TECHNICAL SPECIFICATION

Applications Tractor

Description AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version STANDARD

US Code 94034512

Type TL

Tire Size 420/85 R 38

LI/SS 144 A8/B



Dimensions (U/M US Standard)

Section Width (in) 17.2

Overall Diameter (in) 68.3

Static Loaded Radius (in) 30.9

Rolling Circumference (in) 199.1

SRI 825

Rim Rec W 15 L

Rim Alt W 13 ; W 14 L

ECE E4-106R-000780

TRA Code R-2

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23
30	3390	3960	4510	5070	5620	6160
25	3390	3960	4510	5070	5620	6160
20	3640	4230	4830	5420	6020	6610
5 LT	4560	5300	6050	6790	7540	8280
5 HT	3640	4230	4830	5420	6020	6610