

TECHNICAL SPECIFICATION

Applications Tractor
 Description RIDEMAX IT 696 has a unique tread design that provides excellent grip for road applications, even in winter conditions. It is best suitable for transport and municipality/maintenance applications also thanks to its high-speed feature. The tread design has been specially developed to ensure excellent self-cleaning properties and a low rolling resistance.

Pattern Name RIDEMAX IT 696

Version STANDARD
 US Code 94035106
 Type TL
 Tire Size 480/80 R 34
 LI/SS 164 A8/159 D



Dimensions (U/M US Standard)
 Section Width (in) 18.9
 Overall Diameter (in) 64.3
 Static Loaded Radius (in) 28.7
 Rolling Circumference (in) 192.7
 SRI 775
 Rim Rec W 15 L
 Rim Alt W 16 L

LOAD CAPACITY TABLE (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|-------|-------|
| 40 | 4530 | 5600 | 6560 | 7620 | 8590 | 9640 |
| 30 | 4870 | 6010 | 7040 | 8190 | 9230 | 10360 |
| 25 | 5180 | 6390 | 7500 | 8710 | 9810 | 11020 |
| 20 | 5390 | 6650 | 7790 | 9060 | 10210 | 11460 |