

TECHNICAL SPECIFICATION

Applications Grader
 Description SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

Pattern Name SUPER GRADER

Version STANDARD
 US Code 94035335
 Type TL
 Tire Size 13.00 - 24
 PR 16



Dimensions (U/M US Standard)
 Overall Diameter (in) 50.2
 Static Loaded Radius (in) 23.1
 Rolling Circumference (in) 149.6
 Rim Rec 8.00 TG SDC
 Rim Alt 9.00/1.5 (DC) ; 10.00/VA SDC

LOAD CAPACITY TABLE (lbs)

mph / psi	58
25	7140

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..