

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader

Description RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version STANDARD
US Code 94037247
Type TL
Tire Size 560/60 R 22.5
LI/SS 161 D/158 E



Dimensions (U/M US Standard)

Section Width (in) 21.4
Overall Diameter (in) 49.0
Static Loaded Radius (in) 21.6
Rolling Circumference (in) 148.3
SRI 600
Rim Rec AG 16.00
Rim Alt 16.00 ; 17.00 ; AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3430	3850	4780	5430	6280	7120	7780	8530	9370
40	3730	4190	5200	5920	6830	7750	8470	9280	10200
30	4520	5070	6300	7160	8280	9390	10250	11240	12350
25	5070	5690	7080	8050	9290	10550	11520	12620	13870
15	5890	6610	8220	9350	10800	12260	13380	14670	16110
5	6700	7530	9370	10650	12300	13950	15230	16710	18350