

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader

Description: RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version: STANDARD
 US Code: 94037254
 Type: TL
 Tire Size: 580/65 R 22.5
 LI/SS: 166 D/163 E



Dimensions (U/M US Standard)

Section Width (in): 22.7
 Overall Diameter (in): 52.2
 Static Loaded Radius (in): 22.5
 Rolling Circumference (in): 158.7
 SRI: 625
 Rim Rec: AG 18.00
 Rim Alt: AG 16.00 ; AG 17.00 ; AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3980	4520	5380	6350	7260	8070	9030	9890	10750
40	4330	4920	5840	6900	7890	8760	9820	10760	11680
30	5240	5940	7080	8340	9560	10610	11880	13020	14140
25	5890	6680	7950	9380	10740	11930	13360	14630	15890
15	6830	7760	9240	10900	12470	13860	15510	16990	18460
5	7790	8840	10520	12410	14200	15770	17670	19360	21030