

## TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader

Description: RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

**Pattern Name**      **RIDEMAX FL 693 M**

Version: STANDARD  
 US Code: 94037315  
 Type: TL  
 Tire Size: 710/50 R 26.5  
 LI/SS: 170 D

Dimensions (U/M US Standard)

Section Width (in): 28.6  
 Overall Diameter (in): 54.4  
 Static Loaded Radius (in): 23.9  
 Rolling Circumference (in): 164.3  
 SRI: 650  
 Rim Rec: AG 24.00  
 Rim Alt: AG 20.00



**LOAD CAPACITY TABLE (lbs)**

mph / psi	15	17	23	29	35	41	46	52	58
45	4450	5050	6130	7100	8180	9260	9980	11060	12010
40	4890	5560	6750	7800	8990	10180	10980	12170	13230
30	5930	6720	8170	9450	10890	12330	13290	14730	16000
25	6670	7560	9180	10610	12230	13860	14940	16560	17990
15	7740	8780	10660	12330	14220	16090	17350	19230	20900
5	8820	10010	12150	14050	16190	18340	19760	21910	23810