

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader

Description RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version STANDARD
US Code 94037322
Type TL
Tire Size 560/45 R 22.5
LI/SS 152 D/149 E



Dimensions (U/M US Standard)

Section Width (in) 21.4
Overall Diameter (in) 42.4
Static Loaded Radius (in) 19.1
Rolling Circumference (in) 128.7
SRI 525
Rim Rec AG 16.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	2660	3010	3580	4230	4840	5380	6020	6590	7160
40	2910	3300	3910	4620	5290	5870	6580	7210	7830
30	3520	3990	4740	5600	6400	7110	7970	8730	9480
25	3950	4480	5320	6280	7200	7990	8950	9800	10650
15	4590	5200	6180	7300	8360	9280	10390	11390	12370
5	5210	5920	7040	8320	9510	10570	11840	12960	14090