

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader

Description RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version STANDARD
US Code 94037537
Type TL
Tire Size 650/55 R 26.5
LI/SS 169 D



Dimensions (U/M US Standard)

Section Width (in) 25.4
Overall Diameter (in) 54.7
Static Loaded Radius (in) 23.9
Rolling Circumference (in) 166
SRI 650
Rim Rec AG 20.00

LOAD CAPACITY TABLE (lbs)

| mph / psi | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 4330 | 4920 | 5960 | 6900 | 7950 | 9010 | 9700 | 10760 | 11680 |
| 40 | 4740 | 5380 | 6530 | 7550 | 8700 | 9850 | 10610 | 11770 | 12790 |
| 30 | 5730 | 6500 | 7900 | 9140 | 10530 | 11930 | 12850 | 14240 | 15480 |
| 25 | 6440 | 7310 | 8870 | 10270 | 11840 | 13400 | 14440 | 16000 | 17390 |
| 15 | 7480 | 8490 | 10310 | 11930 | 13750 | 15560 | 16780 | 18590 | 20200 |
| 5 | 8520 | 9670 | 11740 | 13580 | 15650 | 17720 | 19110 | 21170 | 23010 |