

## TECHNICAL SPECIFICATION

**Applications** Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

**Description** AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name AS 504**

Version STANDARD  
 US Code 94038602  
 Type TL  
 Tire Size 6.5/80 - 12  
 PR 6



**Dimensions (U/M US Standard)**

Section Width (in) 6.4  
 Overall Diameter (in) 23.9  
 Static Loaded Radius (in) 10.7  
 Rolling Circumference (in) 72.9  
 Rim Rec 5 J  
 Rim Alt 5 JA

**LOAD CAPACITY TABLE (lbs)**

mph / psi	52
5 FR	2010
15 FR	1710
20 FR	1610
25 FR	1430
5 DW	1390
15 DW	1180
20 DW	1110
25 DW	990

\* Tolerances: Overall Diameter  $\pm$  2% | Section Width  $\pm$  2% | Rolling Circumference  $\pm$  2.5%