

TECHNICAL SPECIFICATION

Applications High Power Tractor

Description AGRIMAX FORCE, the high-end product of BKT, is a radial tire specially designed for agriculture applications with high-power tractors, ensuring top performance and efficiency. AGRIMAX FORCE is a really comfortable tire for both field operations and road transfers; it actually allows to move without the need for increasing the inflation pressure.

Pattern Name **AGRIMAX FORCE**

Version STANDARD

US Code 94038749

Type TL

Tire Size IF 900/60 R 38

LI/SS 184 D

Dimensions (U/M US Standard)

Section Width (in) 36.1

Overall Diameter (in) 80.5

Static Loaded Radius (in) 35.6

Rolling Circumference (in) 236

SRI 975

Rim Rec DW 30 A ; DW 30 B

Rim Alt TW 31 B

ECE E4-106R-000811



LOAD CAPACITY TABLE (lbs)

mph / psi*	9	12	15	17	20	23	29	35
45	8300	9570	11010	12270	13710	14980	16790	18050
from 40 to 25	9130	10520	12100	13490	15080	16470	18450	19800
20	9490	10930	12580	14020	15670	17120	19180	20630
12	9850	11350	13060	14560	16280	17780	19920	21430
5	11580	13350	15370	17130	19150	20910	23420	25200
5 Cyc*	12780	14720	16940	18880	21110	23050	25830	27780
5 HT	9490	10930	12580	14020	15670	17120	19180	20630

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.