

**TECHNICAL SPECIFICATION**

Applications                      Spreader / Harvester  
 Description                      Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**Pattern Name                      AGRIMAX TERIS**

Version                              STANDARD  
 US Code                            94039586  
 Type                                 TL  
 Tire Size                          620/75 R 30 CHO  
 LI/SS                                168 A8/B



Dimensions (U/M US Standard)  
 Section Width (in)              24.6  
 Overall Diameter (in)          66.6  
 Static Loaded Radius (in)      30.7  
 Rolling Circumference (in)    203.5  
 SRI                                  800  
 Rim Rec                            DW 20 B

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	15	20	23	29	35	41	46
30	5690	6550	8020	8770	9630	10490	11360	12350
25	5690	6550	8020	8770	9630	10490	11360	12350
20	6080	7010	8600	9390	10320	11240	12170	13220
10 Cyc.	9380	10800	13250	14470	15890	17320	18750	20370
5 Cyc.	10230	11780	14450	15780	17340	18890	20450	22220