

TECHNICAL SPECIFICATION

Applications Tractor

Description AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version STANDARD

US Code 94040452

Type TL

Tire Size 340/85 R 38

LI/SS 133 A8/B



Dimensions (U/M US Standard)

Section Width (in) 13.9

Overall Diameter (in) 63.1

Static Loaded Radius (in) 28.9

Rolling Circumference (in) 188

SRI 775

Rim Rec W 12

Rim Alt W 11

ECE E4-106R-001477

TRA Code R-2

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23
30	2500	2910	3320	3730	4130	4540
25	2500	2910	3320	3730	4130	4540
20	2680	3120	3550	3990	4430	4860
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2680	3120	3550	3990	4430	4860