

**TECHNICAL SPECIFICATION**

Applications: Trailer  
 Description: FLOTATION RIB IMPLEMENT is a rib pattern tire for trailers in transport applications. It features high flotation capability and ensures significant fuel savings to boost the productivity of your business.

**Pattern Name FLOTATION RIB IMPLEMENT**

Version: STANDARD  
 US Code: 94040469  
 Type: TL  
 Tire Size: 31 X 13.50 - 15  
 PR: 12

Dimensions (U/M US Standard)  
 Section Width (in): 14.2  
 Overall Diameter (in): 30.7  
 Static Loaded Radius (in): 14.1  
 Rolling Circumference (in): 83.8  
 Rim Rec: 10 LB  
 ECE: E11-106R-003389



**LOAD CAPACITY TABLE (lbs)**

mph / psi	75
30	3520

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..