

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
 US Code 94040513
 Type TL
 Tire Size 520/85 R 42
 LI/SS 167 A8/B



Dimensions (U/M US Standard)

Section Width (in) 20.3
 Overall Diameter (in) 76.8
 Static Loaded Radius (in) 33.8
 Rolling Circumference (in) 225.8
 SRI 925
 Rim Rec DW 16 A ; W 16 A ; DD 16
 Rim Alt DW 18 A ; DD 18 ; W 18 A ; DD 18 L

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	35	41	46
30	5000	5820	6650	7460	8280	9090	10220	11180	12010
25	5000	5820	6650	7460	8280	9090	10220	11180	12010
20	5360	6240	7110	7990	8860	9730	10930	11960	12850
5 LT	6710	7800	8910	10000	11100	12190	13690	14980	16100
5 HT	5360	6240	7110	7990	8860	9730	10930	11960	12850