

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name AGRIMAX RT 855

Version: STANDARD
 US Code: 94040537
 Type: TL
 Tire Size: 480/80 R 46
 LI/SS: 164 A8/B



Dimensions (U/M US Standard)

Section Width (in): 18.9
 Overall Diameter (in): 76.2
 Static Loaded Radius (in): 35.2
 Rolling Circumference (in): 231.1
 SRI: 925
 Rim Rec: DW 16 A ; W 16 A ; DD 16
 Rim Alt: W 16 L ; DD 16 L ; DW 16 L

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	20	23	29	35	41	46
30	5060	5810	6560	7310	8060	8720	9350	10250	11000
25	5060	5810	6560	7310	8060	8720	9350	10250	11000
20	5420	6230	7020	7830	8630	9340	10030	10970	11790
5 LT	6790	7790	8800	9800	10800	11680	12550	13730	14770
5 HT	5420	6230	7020	7830	8630	9340	10030	10970	11790