

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

Pattern Name AGRIMAX RT 955

Version: STANDARD
 US Code: 94040636
 Type: TL
 Tire Size: 300/85 R 42
 LI/SS: 144 A8/B

Dimensions (U/M US Standard)

Section Width (in): 11.6
 Overall Diameter (in): 62.1
 Static Loaded Radius (in): 29.3
 Rolling Circumference (in): 190.9
 SRI: 750
 Rim Rec: W 9
 Rim Alt: W 10 ; W 11



LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2540	3270	3960	4320	4630	5070	5500	5860	6150	-
25	2540	3270	3960	4320	4630	5070	5500	5860	6150	-
20	2710	3510	4230	4630	4960	5420	5890	6280	6610	-
5	2880	3620	4450	5280	6120	6300	7040	7780	8520	9260