

TECHNICAL SPECIFICATION

Applications: Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description: AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version: HD
 Type: TT
 Tire Size: 7.5L - 15
 PR: 8



Dimensions (U/M US Standard)

Section Width (in): 8.3
 Overall Diameter (in): 30.1
 Static Loaded Radius (in): 13.9
 Rolling Circumference (in): 89.8
 Rim Rec: 6 LB
 Rim Alt: 5 K ; 5 1/2 J ; 5 1/2 K

Applications: Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description: AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

LOAD CAPACITY TABLE (lbs)

mph / psi	54
5 FR	3550
15 FR	3020
20 FR	2840
25 FR	2540
5 DW	2470
15 DW	2090
20 DW	1970
25 DW	1760

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%