

TECHNICAL SPECIFICATION

Applications Tractor

Description AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version STANDARD
 US Code 94040827
 Type TL
 Tire Size 480/80 R 42
 LI/SS 151 A8/B



Dimensions (U/M US Standard)

Section Width (in) 19.3
 Overall Diameter (in) 74.4
 Static Loaded Radius (in) 33.7
 Rolling Circumference (in) 220.5
 SRI 875
 Rim Rec DW 16 L
 Rim Alt DD 16 L ; W 16 L

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23
30	4190	4870	5560	6240	6920	7600
25	4190	4870	5560	6240	6920	7600
20	4490	5210	5950	6680	7420	8150
5 LT	5610	6530	7450	8370	9280	10200
5 HT	4490	5210	5950	6680	7420	8150