

## TECHNICAL SPECIFICATION

**Applications** Tractor

**Description** AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

**Pattern Name**      **AGRIMAX ELOS**

**Version**                STANDARD  
**US Code**                94040834  
**Type**                     TL  
**Tire Size**                520/85 R 42  
**LI/SS**                    157 A8/B



**Dimensions (U/M US Standard)**

**Section Width (in)**      20.3  
**Overall Diameter (in)**    78.3  
**Static Loaded Radius (in)** 35.6  
**Rolling Circumference (in)** 230.9  
**SRI**                        925  
**Rim Rec**                 DW 16 L  
**Rim Alt**                 DD 18 L ; DW 18 L  
**ECE**                      E4-106R-000793  
**TRA Code**                R-2

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
30	5000	5820	6650	7460	8280	9100
25	5000	5820	6650	7460	8280	9100
20	5360	6240	7110	7990	8860	9730
5 LT	6710	7800	8910	10000	11100	12190
5 HT	5360	6240	7110	7990	8860	9730