

## TECHNICAL SPECIFICATION

Applications                      Spreader / Harvester  
 Description                      Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**Pattern Name                      AGRIMAX TERIS**

Version                              STANDARD  
 US Code                            94040865  
 Type                                 TL  
 Tire Size                          900/60 R 32 CHO  
 LI/SS                                185 A8/182 B



Dimensions (U/M US Standard)

Section Width (in)              34.9  
 Overall Diameter (in)          74.5  
 Static Loaded Radius (in)      33.1  
 Rolling Circumference (in)    225.8  
 SRI                                 925  
 Rim Rec                          DW 27 B  
 Rim Alt                          DW 28 B ; DW 30 B

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	20	23	29	35	41	46	52	58
30	7440	8430	10580	11740	13060	14050	15380	16530	17610	18740
25	8190	9280	11640	12920	14370	15460	16920	18190	19170	20390
20	8760	9930	12470	13820	15390	16560	18110	19470	20510	21820
10 Cyc.	13510	15310	19210	21320	23720	25520	27920	30010	31630	33650
5 Cyc.	14740	16700	20950	23250	25870	27830	30460	32740	34510	36700