

## TECHNICAL SPECIFICATION

Applications                      Trailer / Tanker / Spreader  
 Description                      FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle.

**Pattern Name**                **FL 639**  
 Version                          STANDARD  
 US Code                        94041176  
 Type                              TL  
 Tire Size                        710/40 R 22.5  
 LI/SS                            161 D/172 A8



Dimensions (U/M US Standard)  
 Section Width (in)            28.6  
 Overall Diameter (in)        44.9  
 Static Loaded Radius (in)    19.8  
 Rolling Circumference (in)   137.5  
 SRI                                550  
 Rim Rec                         AG 24.00

**LOAD CAPACITY TABLE (lbs)**

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2980	3440	3900	4740	5480	6320	7150	7700	8540	9280
40	3260	3780	4290	5200	6020	6930	7860	8470	9380	10200
30	3960	4570	5190	6300	7290	8400	9510	10250	11360	12350
25	4440	5140	5830	7080	8190	9440	10680	11520	12760	13870
15	5160	5970	6780	8220	9510	10970	12410	13380	14840	16110
5	5870	6800	7720	9370	10840	12490	14140	15230	16890	18350