

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
 Description FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name FL 630 SUPER

Version STANDARD
 US Code 94041190
 Type TL
 Tire Size 750/60 R 30.5
 LI/SS 181 D



Dimensions (U/M US Standard)
 Section Width (in) 29.7
 Overall Diameter (in) 65.9
 Static Loaded Radius (in) 29.4
 Rolling Circumference (in) 201.4
 SRI 800
 Rim Rec AG 24.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	5300	6130	6960	8450	9780	11260	12750	13750	15230	16560
40	5820	6730	7640	9280	10740	12370	14010	15100	16730	18190
30	7050	8160	9250	11230	13000	14970	16970	18280	20260	22010
25	7930	9160	10390	12620	14590	16820	19050	20530	22760	24730
15	9200	10640	12070	14660	16960	19540	22130	23850	26440	28740
5	10480	12120	13760	16700	19320	22270	25210	27180	30120	32740