

TECHNICAL SPECIFICATION

Applications Compact Loader / Backhoe Loader
 Description AT 625 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. Its extra deep tread ensures increased puncture resistance and durability. AT 625 features excellent traction and stability as well as improved cut and chip resistance.

Pattern Name AT 625

Version STANDARD
 US Code 94041367
 Type TT
 Tire Size 14.9 - 24
 LI/SS 145 A8
 PR 12



Dimensions (U/M US Standard)

Section Width (in) 15.7
 Overall Diameter (in) 49.8
 Static Loaded Radius (in) 22.6
 Rolling Circumference (in) 149.6
 Rim Rec DW 13
 Rim Alt DW 11 ; DW 12 ; DW 13 L

LOAD CAPACITY TABLE (lbs)

mph / psi	42
25	6400

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..